



## 11LF

Shimano Deore XT 10-speed / Continental Prime/ 500Wh / Disc

Article	Inch	Frame size	ColorAmount
1096051	28"	Gents, 50 cm	black matt
1096052	28"	Gents, 55 cm	black matt
1096053	28"	Gents, 60 cm	black matt
1096055	28"	Ladies, 45 cm	black matt
1096056	28"	Ladies, 50 cm	black matt
1096057	28"	Ladies, 55 cm	black matt
1096060	28"	Wave, 45 cm	black matt
1096061	28"	Wave, 50 cm	black matt
1096062	28"	Wave, 55 cm	black matt

Allgemein	
Frame	Aluminium 6061, Continental-Interface
Head set	Chin Haur, tapered 1 1/8" – 1,5" semi-integrated
Fork	Suntour springfork, NEX HLO
Shifting System	Shimano Deore XT
Derailleur	---
Brakes	Shimano Shimano BR-MT200 (160 mm)
Headlight	Busch&Müller Lumotec Avy LED, 40 LUX
Rear light	Busch&Müller, integrated in carrier, LED
Carrier	Racktime Shine Evo Tour, stayless with spring
Saddle	Selle Royal Milo Plus
Seat post	Humpert, Atar, patent, Aluminium, 31,6 mm, 300 mm
Pedals	Marwi SP-823 Aluminium
Kickstand	Pletscher Comp Flex, rear kickstand
Chainguard	Hebie Chainglider Open
Mudguard	SKS, plastic
Other	---
Weight	24,1 kg

Cockpit	
Stem	Levelnine, Aluminium, 1 1/8", a-head, stiff, 31,8 mm, 4-speed bolt
Handlebars	Levelnine, Trekking, Aluminium, 9", 660 mm
Grips	Ergon GP1
Shift lever	Shimano Deore
Brake lever	Shimano, Altus, 3-Finger brake lever

Laufrad/Reifen/Antrieb	
Tires	Continental Contact, 47-622
Rims	Schürmann YAK19 Disc Aluminium double wall rim
Spokes	Niro 2mm
Front Hub	Shimano TX505
Rear Hub	Shimano TX505
Sprocket	Shimano HG50, 11-34 teeth
Chain	Shimano HG 54
Inner bearing	---
Bottom bracket	Lasco Aluminium, 170 mm
Gear ratio (f:r)	42 teeth : 11-34 teeth

### E-Bike Antriebssystem

#### Motor

Continental Prime

48 Volt, mid motor

Output power 250 Watt

#### Display

Continental Display incl. Bluetooth

#### Akku

Continental Framebattery semi-integrated

Energy content: 500 Wh

Voltage: 48 Volt

Capacity: 10.4 Ah